


Decking Screws

C²/DECKING TIMBER SCREWS

Exterior (Green Organic)

Countersunk Head



POZI



EN 14592:2008

CORROSION RATING

1 2 **3** 4 5

Urban & industrial areas with a low salt atmosphere

A premium decking screw using the C2 twin-cut technology. For more information please see page 13.

Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)
--------------	-----------	-------------	-----------------	----------------	--------------------

BOX (DRIVER BIT INCLUDED)

50C2D250BX	4.5 x 50	9 x 2	TX20	250	15
65C2D250BX	4.5 x 65	9 x 2½	TX20	250	18
75C2D250BX	4.5 x 75	9 x 2¾	TX20	250	18

TUB (DRIVER BITS INCLUDED)

50C2D250	4.5 x 50	9 x 2	TX20	250	4
65C2D250	4.5 x 65	9 x 2½	TX20	250	4
65C2D1000	4.5 x 65	9 x 2½	TX20	1,000	1
75C2D250	4.5 x 75	9 x 2¾	TX20	250	4

TIMBAG

50C2DB	4.5 x 50	9 x 2	TX20	175	5
65C2DB	4.5 x 65	9 x 2½	TX20	145	5
75C2DB	4.5 x 75	9 x 2¾	TX20	120	5

TYPE - IDD / IDD / BAG

SUB TYPE - IDD09 / IDD04 / BAG46

Cylinder Head



TX DRIVE



EN 14592:2008

CORROSION RATING

1 2 **3** 4 5

Urban & industrial areas with a low salt atmosphere

A premium decking screw with a reduced cylindrical head to give a concealed finish and patented C2 twin-cut technology.

Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)
--------------	-----------	-------------	-----------------	----------------	--------------------

TUB (DRIVER BIT INCLUDED)

433209	4.5 x 60	9 x 2½	TX15	250	4
--------	----------	--------	------	-----	---

TYPE - IDD

SUB TYPE - IDD07

CLASS/C²// DECKING SCREWS

A2 Stainless Steel

Countersunk Head



POZI



EN 14592:2008

CORROSION RATING

1 2 3 **4** 5

Urban & industrial areas with a moderate salt atmosphere

Superior Corrosion Resistance!

Please note a pilot hole is recommended for all stainless steel screws

All the features and superior performance of the Classic Multi-Purpose Screw manufactured from A2 Stainless Steel. Offering superior corrosion resistance making it ideal for multiple external applications, especially for the construction of decking platforms. Stainless steel must be used where there is corrosive environment and/or the base material has inherent corrosive characteristics e.g. Green Oak.

Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)
--------------	-----------	-------------	-----------------	----------------	--------------------

TUB

50DEXSS250	4.5 x 50	9 x 2	PZ2	250	4
65DEXSS250	4.5 x 65	9 x 2½	PZ2	250	4

TYPE - IDD

SUB TYPE - IDD03

Cylinder Head



TX DRIVE



EN 14592:2008

CORROSION RATING

1 2 3 **4** 5

Urban & industrial areas with a moderate salt atmosphere

Classic decking screw with a reduced cylindrical head to give a concealed finish and single slash for low torque and reduced timber splitting.

Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)
--------------	-----------	-------------	-----------------	----------------	--------------------

TUB (DRIVER BIT INCLUDED)

433187	4.5 x 60	9 x 2½	TX15	250	4
--------	----------	--------	------	-----	---


TYPE - IDD

SUB TYPE - IDD06

SOLO DECKING SCREW

Exterior (Green Organic)

Countersunk Head



POZI




EN 14592:2008

CORROSION RATING

1 2 **3** 4 5

Urban & industrial areas with a low salt atmosphere



An economic but highly effective softwood decking screw. Plated to withstand up to 500 hrs in a salt spray cabinet and designed to give a rapid installation and a secure fixing.

Product Code	Size (mm)	Size (imp.)	Driver Bit Size	Pack Qty (pcs)	Carton Qty (packs)
--------------	-----------	-------------	-----------------	----------------	--------------------

BOX

50SOLOD200	4.5 x 50	9 x 2	PZ2	200	15
60SOLOD200	4.5 x 60	9 x 2½	PZ2	200	15
70SOLOD200	4.5 x 70	9 x 2¾	PZ2	200	16

TUB (2 DRIVER BITS INCLUDED)

60SOLOD1000	4.5 x 60	9 x 2½	PZ2	1,000	1
-------------	----------	--------	-----	-------	---

TYPE - IDD

SUB TYPE - IDD05

C²/DECKING TIMBER SCREW COLLATED SCREWS



SQUARE



EN 14592:2008

PAGE
40